

MaNima Interface

DATASHEET



MaNima Magnus 2

- Master-Slave function.
- Up to 2 universes
- Easy to configure.
- Update the Firmware with the GUI
- Additional features
- Custom API

Live mode

The MaNima LED interface can send live data with ArtNet to digital LED strips or one or both DMX ports.

Custom API

A custom API makes it possible to let your system communicate with the MaNima LED Interface.

Controlling scenes

The recorded scenes can be started by external inputs, DMX; 4-20mA or 0-10V, UDP and MaNima HMI-touchscreen.

Art-Net

The MaNima LED interface can be controlled via ArtNet V1.4. The interface is easy to find and use thanks to the configurable ArtPoll system.

Standalone mode

In Stand-Alone mode, the MaNima LED interface plays a recorded scene from the SD card. The scene can be recorded through Art-Net according to the WYSIWYG principle.

Easy-to-use GUI

The settings of the MaNima LED interface can easily be changed by a user via the MaNima LED interface configurator.

External inputs

Scenes can be started via external inputs. These are digital inputs or analogue inputs; 4-20mA or 0-10V.

Synchronization

Multiple MaNima LED interfaces synchronize when playing scenes through a master and slave setup.

Multiple protocols at once

Due to the available multiple ports, there is also the possibility of sending different protocols over different ports.



Technical Specifications

Weight	<i>360 Gr</i>
Dimensions	<i>90 x 159 x 58 mm</i>
Mounting	<i>Din rail</i>
IP class	<i>IP10</i>
Wiring	<i>Max. 2.5mm² 14 AWG</i>
Connectors	<i>Power: 12-48 VDC terminal connector, Art-Net terminal connector:RJ45 bus, IO port 5-pin input/ Output terminal connector, analogue 6-pin terminal connector, +10 volt terminal connector.</i>
Input voltage	<i>12-48V DC 200mA max</i>
Max. power consumption	<i>9.6W</i>
Channels	<i>1024 Art-Net and/or up to 1024 DMX channels</i>
Ethernet	<i>RJ45 compatible, for 10/100 Base-TX Ethernet with Static IP address or DHCP</i>
Input	<i>DMX512 (2 Inputs) Art-Net MaNima Configurator 5 Digital Inputs 6 Analogue Inputs UDP Custom API</i>
Output	<i>50+ SPI protocols (supported ICs list) DMX512 (2 outputs) SPI (6 outputs) Art-Net</i>
Directives	<i>CE, RoHs</i>
Operating temperature	<i>10°C ~ 60°C</i>
Storage temperature	<i>10°C ~ 60°C</i>
Warranty	<i>5 Years</i>
Gui	<i>MaNima Configurator</i>



SPI Protocols

APA102, APA102_8bit, APA104, APA106, HD107S

BS0901

CX808, CS8812

DM412, DMX

GW6205_400kHz, GW6205_800kHz, GS8208

INK1003

LD1510, LPD6803

MBI6024, MB16120, MY9221, MY9231, MY9291

PC5XS301V0500

SK6812, SK6812RGBW, SK6822, SK8922

SM16703, SM16716, SM16726, SM16904

TM1803, TM1804_400kHz, TM1804_800kHz, TM1809, TM1812, TM1814, TM1914A

UCS1903_400kHz, UCS1903_800kHz, UCS1904, UCS2903, UCS2904, UCS2912, UCS512B3, UCS5603A, UCS8904, UCS9812, UCS8903


WES9412, WES943

WS2801, WS2803, WS2811_400kHz, WS2811_800kHz, WS2812, WS2812B, WS2812S, WS2813, WS2815, WS2818



Connection Diagram

Descriptions of ports from top left to bottom right:



12/48V Input: Connect 12/48 Volts to this connector. DO NOT make short circuit while doing this, since it will seriously damage the MaNima LED Interface.

Digital Inputs: Digital Inputs are inputs used to control the MaNima LED Interface with voltages between +3,3V and +12V. Inputs can be configured using the 'Inputs' tab.

SPI-ports (1-6): These ports are used as outputs for the Data (D) Ground (G) and the Clock (C). Every port has a D,G and a C output. These ports make sure the LEDs will receive the Digital Signal.

SD-Slot: An SD card can be placed inside this slot. All scenes are recorded and saved here.

LAN/Ethernet: To connect to a network, a LAN or Ethernet cable must be connected to the MaNima LED Interface, using this port.

Analog Inputs: These inputs are used as Analog Channels. The +10V is used for these connections (It can also be used for the Digital inputs).

DMX 1-2: These ports are used for devices that need DMX signals..

Models

Functions	Models	MaNima Magnus 2	MaNima Magnus 8	MaNima Magnus 14	MaNima Magnus 20	MaNima Magnus 26
Record/Play 2 Universes	✓	✓	✓	✓	✓	✓
Record/Play 8 Universes	✗	✓	✓	✓	✓	✓
Record/Play 14 Universes	✗	✗	✓	✓	✓	✓
Record/Play 20 Universes	✗	✗	✗	✓	✓	✓
Record/Play 26 Universes	✗	✗	✗	✗	✓	✓
Live playing	✓	✓	✓	✓	✓	✓
Stand-alone playing	✓	✓	✓	✓	✓	✓
Autoloop Scanner	✓	✓	✓	✓	✓	✓
Interface Scanner	✓	✓	✓	✓	✓	✓
Network Configuration	✓	✓	✓	✓	✓	✓
Port Configuration	✓	✓	✓	✓	✓	✓
DMX output	✓	✓	✓	✓	✓	✓
DMX Input	✓	✓	✓	✓	✓	✓
Group Configuration	✓	✓	✓	✓	✓	✓
Digital Inputs	✓	✓	✓	✓	✓	✓
Analog Inputs	✓	✓	✓	✓	✓	✓
Digital outputs	✓	✓	✓	✓	✓	✓
Analog outputs	✓	✓	✓	✓	✓	✓
UDP	✓	✓	✓	✓	✓	✓
ART-NET	✓	✓	✓	✓	✓	✓
Ethernet IP	✓	✓	✓	✓	✓	✓
Custom API	✓	✓	✓	✓	✓	✓
Updating through ethernet	✓	✓	✓	✓	✓	✓
SD-Card	✓	✓	✓	✓	✓	✓



GUI

MaNima LED Interface - □ ×

Scanner Currently editing: ManimaInterface (192.168.1.185)

Device name	IP Address	MAC	Version	Software Version	Identify
ManimaInterface	192.168.1.185	70:B3:D5:DD:90:30	Magnus 8	V 2.0.7	<input type="checkbox"/>

Scanner
Network
Led output
Inputs
DMX

MaNima LED Interface - □ ×

Led output Currently editing: ManimaInterface (192.168.1.186)

Universe mapping Segments

Scanner

Network

Led output

Inputs

DMX

Port 1

Uni: 1
Uni: 2

Universe

TM1914

Port 2

Uni: 3
Uni: 4

Universe

3 - 4

TM1914

Port 3

Uni: 5
Uni: 6

Universe

5 - 6

TM1914

Port 4

Uni: 7
Uni: 8

Universe

7 - 8

TM1914

Port 5

Universe

WS2812

Port 6

Universe

WS2812



Contact Info

MaNima Technologies B.V.

Address:

Hastelweg 260-B
5652 CN, Eindhoven
Netherlands

Contact:

E: info@manima-technologies.com
W: www.manima-technologies.com
T: 040 202 49 04

Dutch chamber of Commerce registration number/KvK-nummer: 71614605

